



TECHNICAL DATA SHEET

PREFACE

Ideal decking oil must meet the challenges made by natural deterioration of wood due to natural atmospheric changes, temperature variations, changes in moisture contents, mould and fungal attacks and ability for water repellency. Also it must have destructive UV rays absorption properties.

PRODUCT INTRODUCTION

NARSO Decking oil is specially formulated to enhance natural beauty of decks and exterior wooden furniture; It is ideal solution for exterior deck and furniture protection and maintenance.

NARSO decking oil contains specially filtered natural vegetable oils and resins. For best results it is added with advanced UV rays absorption additives, anti mold and fungus additives and water repellent additives. NARSO decking oil is penetrating and hardening decking oil.

Uses – Decking, garden furniture, and exterior wood. Virtually it is ideal for any type of wood

SALIENT FEATURES

Maintain natural beauty of wood
Easy to apply.
Ease of maintenance
Economical
Good coverage
Protects wood from atmospheric changes
Offers proper visibility of wood grains
Allows wood to breath
Good water repellency
Protects greying effects
Penetrates deeply in wood forming a monolayer.
Not peelable.

Application

Clean wood and remove loose particles, fibres, previous coatings or paints.
Wood should be smooth and free from any dirt, water etc.
Wood must be dry and moisture contents should below 18-20 %
Apply by brush of good quality. Remove excess oil by rags or brush.
The layer should be uniform.
Apply one or more coats as par requirement.

Do and Don'ts

Wood should be completely dry.
No dirt, fibres, oil be there.
Don't apply to oily wood
Wood must be dried completely.
For resinous wood, Must be dried minimum for six months before application.
Remove paints or coatings by strippers.
Do not apply without removing pervious coatings Do not apply while it is raining.
Do not mix anything with product.Product.is ready to use

Physical and Chemical Properties

Composition	Vegetable Oils, Alkyd resins, solvents, additives
Solid content	40%
Density	.92 to. 94 kg/ ^{m3}
viscosity	3@25 °C
Flash Point	50 °C
Shelf Life	12 Months
Dry film thickness	40 Micron
Drying time	Touch dry 2 to 4 hours
Hard dry	10 to 12 hours
Recoating time	24 hours
Gloss level	Gloss to matt depending upon species of the wood and finishing
Maintenance Time	One year. Depending upon weather conditions
Shades	Natural light brown
Packing	20L, 50 L, 200 L
Coverage	Approx. 60-70 square foot for single coat

PRECAUTIONS

Danger- Flammable substance
Harmful if swallowed
Contains petroleum solvents
Keep away from children and fire
Use only in well ventilated area.
Use respiratory mask and safety goggles.
Avoid contact with skin and eyes.
Close container after use.
If swallowed, seek medical help immediately



Decking Oil for Wood



Decking Oil for Bamboo

Disclaimer

Data presented in this document is in good faith and accurate and best to our knowledge. The data is submitted for information purposes only and without warranty whatsoever. We do not accept any responsibility or liability which may result from the use of this product. This is due to the nature and application of this product. The use and handling etc. of this product are beyond our control. Hence, we do not accept any responsibility and liability.

Manufactured By

Dattashri Enterprises	Phone +91 72489 41841
S. No. 77/8, Kamthe Estates	Cell +91 98220 68688
Dangat Vasti, Shivne	Email dattashri@gmail.com
Pune 411023 India	Website www.dattashri.net